

MODEL - PRO 60

Maximum operating pressure 60 psi (4kg/cm²)
Maximum temperature 325°F (160°C)

MODEL	PLATEN SIZE		MAX BELT WIDTH		WEIGHTS				OVERALL HEIGHT		OVERALL WIDTH (includes side handles)		OVERALL LENGTH	
					TOP HALF		TOTAL							
	IN	MM	IN	MM	LBS	KG	LBS	KG	IN	MM	IN	MM	IN	MM
PRO 60 - RECTANGULAR MODELS														
PRO60R-1440	14 x 40	355 x 1015	36	900	112	51	246	112	16	405	15	380	49	1245
PRO60R-1636	16 x 36	405 x 915	32	800	120	54	274	124	18	455	17	430	52	1320
PRO60R-1654	16 x 54	405 x 1370	48	1200	198	90	424	192	18	455	17	430	70	1780
PRO60R-1852	18 x 52	455 x 1320	48	1200	200	91	435	197	18	455	19	480	69	1750
PRO 60 - RHOMBOID MODELS - All platens built on a 22° bias with a “left hand” lead.														
PRO60-1930	19 x 30	480 x 760	24	600	100	45	225	102	16	405	19	480	51	1295
PRO60-1937	19 x 37	480 x 940	32	800	120	54	270	122	16	405	19	480	58	1475
PRO60-1943	19 x 43	480 x 1090	36	900	146	66	319	145	16	405	19	480	64	1625
PRO60-1950	19 x 50	480 x 1270	42	1050	196	89	420	190	18	455	19	480	72	1830
PRO60-1956	19 x 56	480 x 1420	48	1200	218	99	472	214	19	480	19	480	78	1980

MODEL - PRO 100

Maximum operating pressure 100 psi (7kg/cm²)
Maximum temperature 325°F (163°C)

MODEL	PLATEN SIZE		MAX BELT WIDTH		WEIGHTS				OVERALL HEIGHT		OVERALL WIDTH (includes side handles)		OVERALL LENGTH	
					TOP HALF		TOTAL							
	IN	MM	IN	MM	LBS	KG	LBS	KG	IN	MM	IN	MM	IN	MM
PRO 100 - RECTANGULAR MODELS														
PRO100R-1420	14 x 20	355 x 510	18	450	63	29	142	64	16	405	17	430	29	735
PRO100R-1426	14 x 26	355 x 660	24	600	79	36	174	79	16	405	17	430	35	890
PRO100R-1434	14 x 34	355 x 865	30	750	108	49	233	106	16	405	17	430	44	1115
PRO100R-1842	18 x 42	455 x 1065	38	950	170	77	326	148	19	480	19	480	58	1475
PRO100R-1446	14 x 46	355 x 1170	42	1050	149	68	324	147	20	510	17	430	56	1420
PRO100R-1846	18 x 46	455 x 1170	42	1050	191	87	417	189	20	510	19	480	62	1575
PRO100R-2646*	26 x 46	660 x 1170	42	1050	295	134	652	296	22	560	27	685	62	1575
PRO100R-1852	18 x 52	455 x 1320	48	1200	220	100	475	215	21	535	19	480	69	1750
PRO100R-1454	14 x 54	355 x 1370	50	1250	189	86	400	181	21	535	17	430	70	1780
PRO100R-1864*	18 x 64	455 x 1625	60	1500	316	143	690	313	23	585	19	480	81	2055
PRO 100 - RHOMBOID MODELS - All platens built on a 22° bias with a "left hand" lead.														
PRO100-1924	19 x 24	480 x 610	20	500	98	44	212	96	16	405	19	480	45	1145
PRO100-1930	19 x 30	480 x 760	24	600	110	50	245	111	17	430	19	480	51	1295
PRO100-2830*	28 x 30	710 x 760	24	600	163	74	335	152	17	430	27	685	54	1370
PRO100-1937	19 x 37	480 x 940	32	800	147	67	322	146	18	455	19	480	58	1475
PRO100-2837*	28 x 37	710 x 940	32	800	208	94	454	206	18	455	27	685	62	1575
PRO100-1943	19 x 43	480 x 1090	36	900	156	71	343	156	19	480	19	480	64	1675
PRO100-2243*	22 x 43	560 x 1090	36	900	192	87	420	190	18	455	22	560	65	1660
PRO100-2843*	28 x 43	710 x 1090	36	900	223	101	495	224	20	510	27	685	70	1780
PRO100-1950	19 x 50	480 x 1270	42	1050	217	98	475	215	19	480	19	480	72	1830
PRO100-2850*	28 x 50	710 x 1270	42	1050	285	129	625	283	22	560	27	685	74	1880
PRO100-1956	19 x 56	480 x 1420	48	1200	254	115	551	250	22	560	19	480	79	2005
PRO100-2856*	28 x 56	710 x 1420	48	1200	367	166	800	363	23	585	27	685	81	2055
PRO100-1962*	19 x 62	480 x 1575	54	1350	281	127	610	277	23	585	19	480	84	2135
PRO100-2862*	28 x 62	710 x 1575	54	1350	416	189	922	418	25	635	27	685	87	2210
PRO100-1970*	19 x 70	480 x 1780	60	1500	355	161	773	351	25	635	19	480	94	2385
PRO100-2870*	28 x 70	710 x 1780	60	1500	507	230	1102	500	27	685	27	685	94	2385

• Specifications are approximate and subject to change without notice. • Models with asterisk (*) include side handles, add 6" to overall width.

• Smaller models include in-frame controls. Larger sizes and 3 phase models require remote controls. Optional side carrying handles for smaller PRO 100 models available upon request.